



- Feature :**
- According to JISC 1609 : 1993 AND CNS 5119 general A class specifications.
 - Spectral response close to CIE luminous spectral efficiency.
 - Measuring intensities of illumination in unit of Lux or Foot-candle.
 - Silicon photo diode and filter. • Cosine angular corrected. • Data Hold.

TM-201L



TM-209



TM-209M



Specifications :

TM-201L LED Light Meter	TM-209 LED Light Meter	TM-209M Multi-LED Light Meter
3 1/2 digits LCD with maximum reading 2000	White light LED and whole visible light measuring	6 LED light source and whole visible light measuring: L0 → Standard light source A. L1 → LED white day light. L2 → LED RED light. L3 → LED AMBER(YELLOW) light. L4 → LED GREEN light. L5 → LED BLUE light. L6 → LED PURPLE light. L7~L9 → Default Standard light source A.
	Luminous Intensity Measurement	
	99 records storage capacity	
	Auto power off with disable function	
Max Hold	Max / Min / AVG hold	
Zero adjustment	Real Zero function	
Manual Ranging	Auto ranging	
Range: 200, 2000, 20000, 200000 LUX 20,200, 2000, 20000 FC	Range: 40, 400, 4,000, 40,000, 400,000 LUX 40, 400, 4,000, 40,000 FC	
	Meter Size : 130 x55 x38mm	
	Sensor Size : 80 x55 x25mm	
	Weight : 250g	
±3% (Calibrated to standard incandescent lamp 2856°K and corrected LED day white light) ±8% (other visible light source)	±3% (Calibrated to standard incandescent lamp 2856°K and corrected LED light source) ±6% (other visible light source)	