



Display : • 3 1/2 digits LCD with maximum reading 2000. • Overload indication : "OL"

Functions : • According to JISC1609 : 1993 and CNS 5119 general A class specifications.

- Spectral response close to CIE luminous spectral efficiency.
- Measuring intensities of illumination in unit of Lux or Foot-candle.
- Silicon photo diode and filter.
- Cosine angular corrected.
- Real Zero function.
- Measuring light source include all visible light source.
- USB interface, 7000 Records data logger(TM-203).

TM-203 Datalogging Light Meter



Protection Holster (optional accessory)

Specifications :

- Data hold.
- AVG func.
- Max / Min hold.
- Zero adjustment.
- Auto ranging.
- Auto power off.
- Datalogger.
- Sensor : Silicon photo diode and filter.
- Meter size : 172x56x38mm. (LxWxH)
- Weight : 250g. (including battery)



Measuring range	20, 200, 2000, 20000, 200000 Lux 20, 200, 2000, 20000 Foot-candle										
Accuracy	±3% (Calibrated to standard incandescent lamp 2856°K) ±6% (other visible light source)										
Angle deviation from cosine characteristics	<table border="1"> <tr><td>10°</td><td>± 0.5%</td></tr> <tr><td>30°</td><td>± 2%</td></tr> <tr><td>50°</td><td>± 3%</td></tr> <tr><td>60°</td><td>± 6%</td></tr> <tr><td>80°</td><td>± 25%</td></tr> </table>	10°	± 0.5%	30°	± 2%	50°	± 3%	60°	± 6%	80°	± 25%
10°	± 0.5%										
30°	± 2%										
50°	± 3%										
60°	± 6%										
80°	± 25%										

TM-204 Light Meter



Specifications :

- Data hold.
- Max hold.
- Zero adjustment.
- Sensor : Silicon photo diode and filter.
- Meter size : 172x56x38mm. (LxWxH).
- Weight : 250g. (including battery).

TM-205 Light Meter (Auto- Ranging)



Specifications :

- Data hold.
- MAX / MIN.
- Zero adjustment.
- Auto ranging.
- Auto power off.
- Sensor : Silicon photo diode and filter.
- Meter size : 172x56x38mm. (LxWxH)
- Weight : 250g. (including battery)

Measuring range	200, 2000, 20000, 200000 Lux 20, 200, 2000, 20000 Foot-candle										
Accuracy	±3% (Calibrated to standard incandescent lamp 2856°K) ±8% (other visible light source)										
Angle deviation from cosine characteristics	<table border="1"> <tr><td>10°</td><td>±0.5%</td></tr> <tr><td>30°</td><td>±2%</td></tr> <tr><td>50°</td><td>±3%</td></tr> <tr><td>60°</td><td>±6%</td></tr> <tr><td>80°</td><td>±25%</td></tr> </table>	10°	±0.5%	30°	±2%	50°	±3%	60°	±6%	80°	±25%
10°	±0.5%										
30°	±2%										
50°	±3%										
60°	±6%										
80°	±25%										

Measuring range	20, 200, 2000, 20000, 200000 Lux 20, 200, 2000, 20000 Foot-candle										
Accuracy	±3% (Calibrated to standard incandescent lamp 2856°K) ±6% (other visible light source)										
Angle deviation from cosine characteristics	<table border="1"> <tr><td>10°</td><td>±0.5%</td></tr> <tr><td>30°</td><td>±2%</td></tr> <tr><td>50°</td><td>±3%</td></tr> <tr><td>60°</td><td>±6%</td></tr> <tr><td>80°</td><td>±25%</td></tr> </table>	10°	±0.5%	30°	±2%	50°	±3%	60°	±6%	80°	±25%
10°	±0.5%										
30°	±2%										
50°	±3%										
60°	±6%										
80°	±25%										